



VERTICAL SLICER AERATOR (VSA-21)

PRODUCT INFORMATION

Vertical Slicer Aerator (VSA) is a dual purpose implement. The VSA is available with dual rotor shafts and each rotor shaft is equipped with carbide tipped blades. The blades on the front rotor shaft are seven and one half inches in diameter, one eighth inch thick and spaced four inches apart. The rear rotor blades are five inches in diameter, one sixteenth inch thick and spaced one inch apart. The VSA-21 can also be equipped with one rotor assembly. The unit comes fully assembled with exception to the handle bar assembly. The handle bar assembly is in two pieces which must be bolted together (fasteners provided) and then attached to the main frame.

HOW TO ORDER

Select base unit and then make one selection from Section A.

VSA-21 Base Unit-----Price \$1695.00

Section A – select one option

A* - Verti-cut rotor is equipped with 4” Carbide tipped blades on 1” Spacing -----\$600.00

or

B* – Vertical Slice rotor is equipped with 7” Carbide tipped blades on 4” Spacing -----\$700.00

or

C* – Dual rotor shaft – front rotor “B” and rear rotor “A” options -----\$1500.00

<u>Specifications</u>			
Engine:	5.5 HP Honda	Wheels:	8" x 1-3/4" flat free with greasable bearings
Model:	VSA -21	Weight:	140 lbs.
Swatch:	21"	Width:	27-1/2" (storage position); 27-1/2" (operating position)
Capacity:	Up to 10,000 square feet per hour	Height:	28-1/2" (storage position); 42" (operating position)
Drive:	Single V-belt	Length:	28" (storage position); 42" (operating position)
Clutch:	V-belt idler type, controlled from operator's position	Working Depth:	Front rotor – 2" Rear rotor – 1/2"
		Blades:	Front rotor – 7 1/2" Carbide tipped Rear rotor – 5" Carbide tipped

1545 Stanley Ave - Andalusia, Alabama 36420
 Phone: 334-488-3939 www.turfprideusa.com Fax: 888-427-7605
 Prices and specifications subject to change without notice.
 All prices are FOB Andalusia, AL